

XKS

Elettropompe sommergibili in acciaio inox Water Submersible Pumps

Applicazione

- Elettropompa leggera e maneggevole, la sua affidabilità è garantita da una doppia protezione contro infiltrazioni, ottenuta con tenuta meccanica e guarnizione. Tutti i componenti delle elettropompe XKS sono stati realizzati seguendo le direttive WEE, ROHS, PAHS, che ne garantiscono la totale sicurezza

UTILIZZO

- Temperatura del liquido fino a: +35° C.
- Temperatura ambiente fino a: 40° C.

DATI TECNICI

- Alimentazione 230-240V/50Hz
- Aspirazione 25/32mm
- Cavo H05RN-F 10mt

Application

- It is mainly used for water drainage in the pond, miniature landscape, bathing, domestic cultivation and solar water supply place etc. It can also be used for small equipment and water supply system for facilities.

OPERATING LIMITS

- Fluid temperature up to 35° C.
- Ambient temperature up to 40° C.

TECHNICAL DATA

- Supply power 220-240V/50Hz
- Outlet 25/32mm
- Cable H05RN-F 10m



Dati tecnici | Technical Data

Mod. Acqua pulita Mod. Clean Water	Alimentazione Supply power	Potenza Power		Prevalenza max. Max. head	Portata max. Max. flow	Max diam particelle Max. dia. of particle	Preso Outlet	Cavo Cable	Codice Code	€ cad € each
		kW	HP							
XKS250S	220-240V/50Hz	0.25	0.33	5.5mt	5.5m³/h	5mm	25/32mm	H05RN-F 10mt	10XKS250S	104,00
XKS350S	220-240V/50Hz	0.35	0.50	7mt	8m³/h	5mm	25/32mm	H05RN-F 10mt	10XKS350S	110,00

Mod. Acqua Carica Mod. Dirty Water	Alimentazione Supply power	Potenza Power		Prevalenza max. Max. head	Portata max. Max. flow	Max diam particelle Max. dia. of particle	Preso Outlet	Cavo Cable	Codice Code	€ cad € each
		kW	HP							
XKS400SW	220-240V/50Hz	0.40	0.60	5.5mt	8m³/h	35mm	25/32mm	H05RN-F 10mt	10XKS400SW	125,00
XKS750SW	220-240V/50Hz	0.75	1.00	8mt	11.5m³/h	35mm	25/32mm	H07RN-F 10mt	10XKS750SW	142,00

Dimensioni imballo | Package information

Modello Model	GW (Kg)	L (mm)	W (mm)	H (mm)
XKS250S	4	320	320	420
XKS350S	5	320	320	420
XKS400SW	5	344	375	450
XKS750SW	7	344	375	450

